

Furance Number	Furance Type	Furance Process Capabilities	Max Weight (Pounds)	Work Zone Dimentions	Class 2 (±10°F) Range
101	Freezer/ Temper	Cryo-Temper, Thermal Cycling, Freezing	100	10"x16"x12"	
104	Freezer/ Temper	Cryo-Temper, Thermal Cycling, Freezing	1000	28" X 35" X 95"	
110	Liquid Nitrogen	Cyro	10	Liquid Nitrogen	
112	Freezer / Temper	Cryo-Temper, Thermal Cycling, Freezing	200	38"x34"x36"	
206	Electric Recirculated Air	Temper/ Aging	300	23"x16"x13"	
208	Electric Recirculated Air	Temper/ Aging	300	22"x28"x24"	
210	Electric Recirculated Air	Aluminum Solution, Tempering, Aging	500	25"x29"x40"	600-1000°F
215	Electric Recirculated Air	Temper/ Aging	300	24"x32"x36"	300-1150°F
216	Electric Recirculated Air	Aluminum Solution, Tempering, Aging	300	24"x32"x36"	260-1160°F
218	Electric Recirculated Air	Aluminum Aging	5000	36"x40"x68"	
219	Electric Recirculated Air	Temper/ Aging	200	12"x18"x16"	300-1250°F
220	Electric Recirculated Air	Temper/ Aging	200	12"x18"x16"	300-1075°F
223	Electric Recirculated Air	Aluminum Aging	5000	46"x60"X105"	
225	Electric Recirculated Air	Temper/ Aging	3000	42.5" Dia x65"	
226	Electric Recirculated Air	Temper/ Aging	3000	32 Dia"x72"	600-1400°F
228	Electric Recirculated Air	Aluminum Solution, Tempering, Aging	3500	36"x48"x72"	
229	Electric Recirculated Air	Aluminum Ageing	400	65"x45"x45"	
232	Electric Recirculated Air	Temper/ Aging	300	13"x24"x24"	
233	Electric Recirculated Air	Temper/ Aging	250	13"X24"x24"	
234	Electric Recirculated Air	Temper/ Aging	250	13"x24"x24 "	
237	Electric Recirculated Air	Temper/ Aging	300	29"x47"x18"	
240	Electric Recirculated Air	Temper/ Aging	3000	30"Dia X 72"	500-1350°F

241	Electric Recirculated Air	Temper/ Aging	1000	40"X37"X26"	
242	Electric Recirculated Air	Temper/ Aging	250	13"X20"X33"	600-1300°F
243	Electric Recirculated Air	Temper/ Aging	250	13"X20"X33"	
244	Electric Recirculated Air	Temper/ Aging	250	13"X20"X33"	
246	Electric Recirculated Air	Temper/ Aging/ Protective Temper/ Protective Age	1000	22" Dia X 36"	
249	Electric Recirculated Air	Aluminum Aging	3000	33" x 71.5" x 77.5"	
250	Electric Recirculated Air	High Temperature Oxidation	100	20"x20"x30"	
303	Salt Pot	Hardening/ Mar-Quench/ Austemper	25	16" Dia X 34"	
307	Salt Pot	Hardening/ Mar-Quench/ Austemper	25	16" dia x 34"	
310	Natural Gas Integral Quench	Oil Quench/ Water Quench/ Hardening/ Carburizing/ Carbonitride/ Titanium Solution	1000	18"x24"x42"	
314	Natural Gas Recirculated Air	Temper/ Aging	1500	24"x30"x48"	600-1200°F
315	Natural Gas Recirculated Air	Temper/ Aging	1500	24"x30"x48"	800-1400°F
317	Natural Gas Integral Quench	Oil Quench/ Hardening/ Carburizing/ Carbonitride/ Titanium Solution	300	20"x20"x30"	
318	Natural Gas Integral Quench	Oil Quench/ Hardening/ Carburizing/ Carbonitride/ Titanium Solution	2000	22"x30"x48"	
319	Natural Gas Integral Quench	Oil Quench/ Hardening/ Carburizing/ Carbonitride/ Titanium Solution	2000	30"x30"x48"	
320	Natural Gas Integral Quench	Oil Quench/ Hardening/ Carburizing/ Carbonitride/ Titanium Solution	2000	30"x30"x48"	
321	Natural Gas Recirculated Air	Temper/ Aging	2000	30"x30"x48"	
322	Natural Gas Recirculated Air	Temper/ Aging	2000	30"x30"x48"	300-1400°F

323	Natural Gas Recirculated Air	Temper/ Aging	2000	30"x30"x48"	500-1400°F
324	Natural Gas Recirculated Air	Temper/ Aging	2000	30"x30"x48"	300-1400°F
502	Vacuum	Hardening/ Solution Anneal/ In Process Anneal/ Fuse/ Protective Aging/ Protective Tempering/	1000	21"x30"x46"	
504	Vacuum	Hardening/ Solution Anneal/ In Process Anneal/ Fuse/ Protective Aging/ Protective Tempering/	300	13"x10"x24"	600-2050°F
506	Vacuum	Hardening/ Solution Anneal/ In Process Anneal/ Fuse/ Protective Aging/ Protective Tempering/	2500	34"x43"x43"	900-1800°F
508	Vacuum	Hardening/ Solution Anneal/ In Process Anneal/ Fuse/ Protective Aging/ Protective Tempering/	300	10"x15"x28"	
510	Vacuum	Hardening/ Solution Anneal/ In Process Anneal/ Fuse/ Protective Aging/ Protective Tempering/	2500	34"x32"x46"	
511	Vacuum	Hardening/ Solution Anneal/ In Process Anneal/ Fuse/ Protective Aging/ Protective Tempering/	750	24"x24"x36"	
Various Hardness Testing					



